


LED PANEL SORTIMENT



LEDsystem Panel

Ceiling recessed luminaire, LED, 49W power,
Electronic control gear

On request:

Dimmable electronic control gear DALI (10-100%)
Tuneable white, CCT adjustable from 3000K to 6500K

Housing: sheet steel

Frame: Sheet steel

Diffuser: opal PMMA or microprisma (combination
opal+microprisma PMMA)

Also possible in MINI version 300x300

net lumen output (at Ta = 25 °C) (lm)	power consumption (W)	color rendering index CRI (Ra)	correlated color temperature CCT (K)
4050	49	80	3000
4400	49	80	4000



Freyn

Ceiling recessed luminaire LED
Electronic control gear

On request:

Dimmable electronic control gear DALI (10-100%)

Housing: sheet steel

Diffuser: microprismatic PMMA

On request:

Trimless frame

net lumen output (at Ta = 25 °C) (lm)	power consumption (W)	color rendering index CRI (Ra)	correlated color temperature CCT (K)
3000	44	80	3000
3150	44	80	4000
4400	56	80	3000
4650	56	80	4000

Also possible as 36W



Relax XTP IP65

Ceiling recessed LED 600x600
Electronic control gear

On request:

Dimmable electronic control gear DALI(10-100%)

Housing:sheet steel

Frame: extruded aluminium

Diffuser: PMMA OPAL+PMMA Diamond microprisma

net lumen output (at Ta = 25 °C) (lm)	power consumption (W)	color rendering index CRI (Ra)	color temperature CCT (K)
3300	49	80	3000
3400	49	80	4000



Modul BOX

Suspended or Surfaced LED luminaire

Electronic control gear

On request:

Dimmable electronic control gear DALI (10-100%)

Housing: sheet steel




Frame: extruded aluminium profile

Diffuser: opal PMMA + PMMA Diamond microprisma

Black (RAL 9005) + silver grey (RAL 9006)


Other colors on request




net lumen output (at Ta = 25 °C) (lm)	power consumption (W)	color rendering index CRI (Ra)	color temperature CCT (K)
950	14	>80	3000
950	14	>80	4000
4100	52	>80	3000
4100	52	>80	4000



Saiph
Ceiling recessed or surfaced
Electronic control gear
On request:
Dimmable electronic control gear DALI (10-100%), 1-10V (5-100%)
Housing: sheet steel
Diffuser: opal plastic
Top sheets: plain sheet steel



net lumen output (at Ta = 25 °C) (lm)	power consumption (w)	color rendering index CRI (Ra)	correlated color temperature CCT (K)
3000	34	90	3000
3000	34	90	4000







Baten
Ceiling recessed luminaire
Electronic control gear
On request:
Dimmable electronic control gear DALI (1-100%)
Housing: sheet steel
Diffuser: linear microprisma
Heatsink: aluminium profile

net lumen output (at Ta = 25 °C) (lm)	power consumption (w)	color rendering index CRI (Ra)	correlated color temperature CCT (K)
2800	36	80	3000
3000	36	80	4000





Vega
Ceiling recessed luminaire
Electronic control gear
On request:
Dimmable electronic control gear DALI (10-100%)
Housing: sheet steel
Reflector: aluminium
Diffuser: opal PMMA

net lumen output (at Ta = 25 °C) (lm)	power consumption (w)	color rendering index CRI (Ra)	color temperature CCT (K)
3050	45	>80	3000
3200	45	>80	4000





Vega Exclusive
Suspended or recessed luminaire
Blue Ambient LED light
Dimmable electronic control gear DALI (10-100%)
Housing: sheet steel
Reflector: aluminium sheet
Diffuser: acryl satine

net lumen output (at Ta = 25°C) (lm)	power consumption (W)	colour rendering index CRI (Ra)	colour temperature CCT (K)
2100	27	>80	3000
2200	27	>80	4000
3050	45	>80	3000
3200	45	>80	4000





Mirzam
Electronic control gear
On request:
Dimmable electronic control gear DALI (13-100%)
Housing: sheet steel
Diffuser: opal textured plastic

net lumen output (at Ta = 25°C) (lm)	power consumption (W)	color rendering index CRI (Ra)	correlated color temperature CCT (K)
3500	43	80	3000
3700	43	80	4000



Terzo
Ceiling recessed
Electronic control gear
Dimmable electronic control gear DALI (10-100%)
Housing: sheet steel
Diffuser: vacuum moulded opal polycarbonate
Parabolic louvre: anodized polished aluminium

net lumen output (at Ta = 25 °C) (lm)	power consumption (W)	color rendering index CRI (Ra)	color temperature CCT (K)
4250	49	80	3000
4550	49	80	4000



Becrux
Recessed luminaire
Electronic control gear
On request:
Dimmable electronic control gear DALI (10-100%)
Housing: sheet steel
Shade: polished stainless steel
Decorative frame: sheet steel

net lumen output (at Ta = 25°C) (lm)				power consumption (W)	colour temperature CCT (K)				color rendering index CRI (Ra)		
cool white	neutral white	warm white	warm white / cool white		cool white	neutral white	warm white	warm white / cool white	warm white	neutral white	cool white
1800	1800	1300	1500	28	5700	4000	3000	3000-5700	80		70

Also possible as 40W, 35W, 50W, 70W, 77W, 100W, 110W